



CHALLENGER

Challenger 44030-44060 Heavy-Duty Truck Lift

Heavy-Duty Chain-Driven 4-Post Lift

30,000 LBS. CAPACITY

Contact for Pricing

We designed our 30,000 lb. to 60,000 lb. lifts as an economic high capacity lifting solution in a traditional 4-post design. Diamond plated anti-skid runways and ramps provide for positive vehicle traction.

30,000 lbs.

CAPACITY

68"

RISE HEIGHT

105 s

FULL RISE

3HP, 208-230v Single Phase

POWER

FEATURES

- 30,000 lb. to 60,000 lb. capacity 4-post
- 32" wide runways aid for drive-on confidence
- Single-point air actuated lock release allows technicians to disengage column locks simultaneously
- 310" to 430" max wheelbase
- 10 lock positions provide maximum head room for working underneath vehicles (40K-60K)
- Diamond-plate approach ramps for positive vehicle traction

SPECIFICATIONS

SPECIFICATION	44030
Lifting Capacity	30,000 lbs.
Rise Height	68"
Speed of Rise	105 s
Overall Length	24' 7.5"
Overall Width	12' 5.5"
Overall Height	92"
Inside Columns	132.5"
Between Columns	233.75"
Runway Height	9"
Width of Runways	24"
Width Between Runways	54" – 75"
Width Between Runways with jacks	NA
Max Wheelbase	230"
Motor / Voltage	3HP, 208-230v Single Phase
Amps	30

Specifications published by the Challenger factory and subject to change. Source: challengerlifts.com.