



CHALLENGER

Challenger CL16 Two-Post Lift

16K Heavy-Duty Two-Post Adjustable Lift

16,000 LBS. CAPACITY

Contact for Pricing

Challenger's 16K Heavy-Duty Two-Post lift offers unparalleled flexibility and safety, making it the ultimate partner for all your automotive needs. With a capacity of 16,000 lbs. and featuring 3-stage arms, this lift can handle a variety of vehicles, from select standard cars, trucks, and SUVs to most Electric and commercial-fleet vehicles. It also features low-profile pickup pads, along with multiple height and width options.

16,000 lbs.
CAPACITY

**Min. 75.5" Max.
81.5"**
RISE HEIGHT

62s
FULL RISE

3HP, 1Ph, 60Hz, 208/230v
POWER

OVERVIEW

By investing in Challenger's Heavy-Duty Two-Post lifts, you're not just buying equipment but investing in your business. These lifts are built to last and will withstand even the most demanding fleet maintenance needs, saving you time and money in the long run. So why settle for anything less than the best? Choose Challenger's Heavy-Duty Two-Post lifts and experience the ultimate in performance and safety.

FEATURES

- Single-point air actuated lock release allows the technician to disengage both columns simultaneously
- 60" lifting carriage design increases lift life
- Oversized 5" diameter steel pulley and heavy-duty 3/8" cable reduces stress on equalization system and increases cable life
- Adjustable width and symmetrical design allow easy access to the vehicle's interior

SPECIFICATIONS

SPECIFICATION	CL16-0-3S
Lifting Capacity	16,000 lbs.
Lift Configuration	Symmetric
Arm Configuration	3-Stage Front/Rear
Rise Height (Maximum with Stack Adapters)	Min. 75.5" Max. 81.5"
Rise Time	62s
Overall Width Options	166.75", 160.75", 154.75"
Overall Height Options	162", 168", 174"
Between Columns	120", 126", 132"
Drive-Thru Clearance	104.25", 110.25", 116.25"
Screw Pad Height	Min. 5" Max. 6.5"
Motor/Voltage	3HP, 1Ph, 60Hz, 208/230v
Air Supply Required	90-120 psi
Floor to Overhead Switch	155", 161", 167"
Min. Ceiling Height Required	13'8", 14'2", 14'8"
Description	16K Standard
Maximum Load Per Arm	4,000 lbs.
Arm Reach	Min. 36.625" Max. 75"

Specifications published by the Challenger factory and subject to change. Source: challengerlifts.com.