



## CHALLENGER

# Challenger Lift CL10 Series

10K Versymmetric® Two-Post Adjustable Lift

**10,000 LBS. CAPACITY**

## Contact for Pricing

We also offer the CL10AV3 in several configurations to meet your service application needs. A drive-on pad option provides the quickest vehicle spotting for express bays. Our added Quick Cycle™ models can rise in just 27 seconds and lower in only 17 seconds. Quick Cycle™ technology's increased lift speed will drastically boost your service potential. Adjustable height and width options are also available.

**10,000 lbs.**  
CAPACITY

**74.125"**  
RISE HEIGHT

**38 s**  
FULL RISE

**2HP, 208v-230v, 60Hz, 1Ph**  
POWER

## OVERVIEW

Along with our adjustable 2-Post width options, our new EV Kit prepares you to lift all vehicles safely and correctly.

## FEATURES

- Contact Your Rep Manuals CL10A
- Oversized 5 in. diameter pulley and heavy duty 5/16 in. cable reduces stress on equalization system and increases cable life
- 10,000 lbs. lift capacity
- 48 in. elongated carriage design increases lift life

## SPECIFICATIONS

| SPECIFICATION                      | CL10AV3                       |
|------------------------------------|-------------------------------|
| Lifting Capacity                   | 10,000 lbs.                   |
| Lift Configuration                 | Standard                      |
| Arms                               | 3-stage front/3-stage rear    |
| Rise Height                        | 74.125"                       |
| Speed of Rise                      | 38 s                          |
| Overall Width                      | 11' 6.5" / 12' .5" / 12' 6.5" |
| Overall Height                     | 11' 2" or 11' 8"              |
| Overall Height (Cylinder Extended) | 11' 11"                       |
| Inside Columns                     | 110" / 116" / 122"            |
| Drive-Thru Clearance               | 100" / 106" / 112"            |
| Screw Pad Height                   | 3.875" – 6.125"               |
| Motor / Voltage                    | 2HP, 208v-230v, 60Hz, 1Ph     |
| Floor to Overhead Switch           | 10' 8.5" – 11' 2.5"           |
| Ceiling Height Required            | 12'                           |
| ALI/ETL Certified                  | Yes                           |
| 2' Height Extension Available      | Yes                           |
| 3' Height Extension Available      | Yes                           |
| Front Arm Reach                    | 20" – 42"                     |
| Rear Arm Reach                     | 37.625" – 60"                 |

Specifications published by the Challenger factory and subject to change. Source:  
[challengerlifts.com](http://challengerlifts.com).