



CHALLENGER

Challenger Lift CLFP9

9K Two-Post Lift / Open-Top / Floor Plate

9,000 LBS. CAPACITY

Contact for Pricing

With a 9,000 lb. capacity and 10' 7/8" overall column height, Challenger's CLFP9 2-post is ideal for low ceiling applications. 3-stage front and 3-stage rear arms provide maximum sweep, arm retraction and reach. A low-profile drive-over floor plate allows for easy vehicle positioning, which makes it great for home enthusiast garages or professional service shops. The CLFP9 also features double-telescoping screw footpads, a durable powder coat finish and plated arm pins.

9,000 lbs.
CAPACITY

78.125"
RISE HEIGHT

50 s
FULL RISE

2HP, 208v-230v, 60Hz, 1Ph
POWER

OVERVIEW

9,000 lb. lift capacity 10' 7/8" overall column height is ideal for servicing vehicles in a low ceiling height Low profile drive-over floor plate for easy vehicle positioning 3-stage front and 3-stage rear arms accommodate a wide range of common cars, trucks, vans as well as SUVs within the same service bay Electric/hydraulic heavy-duty chain lifting operation with cable equalization to reduce ceiling height requirement Dual-point mechanical pull-lock...

FEATURES

- 10' 7/8" overall column height is ideal for servicing vehicles in a low ceiling height
- 3-stage front and 3-stage rear arms accommodate a wide range of common cars, trucks, vans as well as SUVs within the same service bay
- Premium double telescoping screw pads adjust to multiple heights minimizing the need for adapters
- Low profile drive-over floor plate for easy vehicle positioning
- Electric/hydraulic heavy-duty chain lifting operation with cable equalization to reduce ceiling height requirement

SPECIFICATIONS

SPECIFICATION	CLFP9
Lifting Capacity	9,000 lbs.
Lifting Configuration	Symmetric
Arms	3-stage front/3-stage rear
Rise Height	78.125"
Speed of Rise	50 s
Overall Width	137.5"
Overall Height	120.875"
Overall Height (Cylinder Extended)	120.875"
Inside Columns	109"
Drive-Thru Clearance	98.187"
Screw Pad Height	4" / 5.875"
Motor / Voltage	2HP, 208v-230v, 60Hz, 1Ph
Floor to Overhead Switch	–
Ceiling Height Required	10' 2"
ALI/ETL Certified	–
Front Arm Reach	24.5" / 44.5"
Rear Arm Reach	24.5" / 44.5"
2' Height Extension Available	–
3' Height Extension Available	–

Specifications published by the Challenger factory and subject to change. Source:
challengerlifts.com.