



CHALLENGER

Challenger Lift SA10

10K Two-Post Lift

10,000 LBS. CAPACITY

Contact for Pricing

10,000 lb. lift capacity 3-stage front arms provide greater sweep for versatility and ease of spotting Can be installed in either symmetric or asymmetric position, depending on your service needs Premium double telescoping screw pads adjust to multiple heights minimizing the need for adapters Adjustable heights and widths provide versatility at installation for service facilities with special constraints Single-point mechanical lock release system allows technician to disengage both columns...

10,000 lbs.
CAPACITY

74.5"
RISE HEIGHT

43 s
FULL RISE

2HP, 208v-230v, 60Hz, 1Ph
POWER

FEATURES

- 3-stage front arms provide greater sweep for versatility and ease of spotting
- Adjustable heights and widths provide versatility at installation for service facilities with special constraints
- Premium powder coat finish provides long-lasting durability
- Premium double telescoping screw pads adjust to multiple heights minimizing the need for adapters
- Single-point mechanical lock release system allows technician to disengage both columns simultaneously

SPECIFICATIONS

SPECIFICATION	SA10
Lifting Capacity	10,000 lbs.
Lifting Configuration	Symmetric
Arms	3-stage front/2-stage rear
Rise Height	74.5"
Speed of Rise	43 s
Overall Width	129" / 135"
Overall Height	136.5" / 142.5"
Overall Height (Cylinder Extended)	142.5"
Inside Columns	106.75" / 112.75"
Drive-Thru Clearance	92.75" / 98.75"
Screw Pad Height	4.75" / 6.875"
Motor / Voltage	2HP, 208v-230v, 60Hz, 1Ph
Floor to Overhead Switch	131.125" / 137.125"
Ceiling Height Required	12'
ALI/ETL Certified	Yes
2' Height Extension Available	Yes
Front Arm Reach	22.375" / 41.5"
Rear Arm Reach	38.25" / 59"

Specifications published by the Challenger factory and subject to change. Source:
challengerlifts.com.