



CHALLENGER

Challenger VLE10 Versymmetric Two- Post Lift

10K Versymmetric® VLE Two-Post Lift

10,000 LBS CAPACITY

Contact for Pricing

Challenger adds the industry leading Versymmetric® Technology to the popular economy grade 10,000 lb 2-post lift, the LE10. Expand your service capabilities with the VLE10's ability to lift a wide range of vehicles, from small passenger cars to SUV's and pick-up trucks within rated capacity.

10,000 lbs
CAPACITY

74.75"
RISE HEIGHT

44s
FULL RISE

2HP, 208v-230v, 60Hz, 1Ph
POWER

OVERVIEW

Lifting Capacity 10,000 lbs Lift Configuration Symmetric and Asymmetric Arm Configuration 3-Stage Versymmetric® Front/2-Stage Rear Max Load Per Arm 2500 lbs Rise Height (screw pads at highest position) 74.75" Overall Height Standard: 143.875" Extended Height: 167.875" Overall Width 131.625" Drive-Thru Clearance 98.375" Floor to Overhead Switch Standard: 137" Extended Height: 161" Front Arm Reach 22.3125"-39.375" Rear Arm Reach 38.375"-55.375" Screw Pad...

FEATURES

- 3-Stage Versymmetric® front arms and 2-Stage rear arms provide a wide arm sweep for asymmetric and symmetric lifting in the same service bay
- Double telescoping screw pads with rubber foot pad
- Premium powder coat finish provides long-lasting durability
- 11.875" standard height fits in service bays with 12' ceiling height
- Jacketed pulley-less single-point mechanical lock release system that was once exclusive to our CL series lifts are now standard on the VLE10

SPECIFICATIONS

SPECIFICATION	VLE10 VERSYMMETRIC TWO-POST LIFT
Lifting Capacity	10,000 lbs
Lift Configuration	Symmetric and Asymmetric
Arm Configuration	3-Stage Versymmetric® Front/2-Stage Rear
Rise Height (screw pads at highest position)	74.75"
Rise Time	44s
Overall Width	131.625"
Overall Height	Standard: 143.875" Extended Height: 167.875"
Between Columns	110.25"
Drive-Thru Clearance	98.375"
Screw Pad Height	4.25"-6.75"
Motor/Voltage	2HP, 208v-230v, 60Hz, 1Ph
Floor to Overhead Switch	Standard: 137" Extended Height: 161"
Ceiling Height Required	Standard: 12' Extended Height 14'
Max Load Per Arm	2500 lbs
Front Arm Reach	22.3125"-39.375"
Rear Arm Reach	38.375"-55.375"

Specifications published by the Challenger factory and subject to change. Source:
challengerlifts.com.