



MOHAWK

Mohawk 800 Series Wireless Mobile Column Lift

Wireless Mobile Column Lift

Contact for Pricing

The Mohawk 800 Series Mobile Column Lifts provide 14,000- or 19,000-pound capacity per column , allowing total lift configurations of 56,000 or 76,000 pounds with a set of four . Each column can operate individually, in pairs, or as a synchronized group of up to eight, and the compact design lets a single operator roll the columns into position and transform any flat surface into a fully functional service bay within minutes .

60" per min.
FULL RISE

24 VDC Nominal
POWER

OVERVIEW

The Mohawk 800 Series delivers fully wireless lifting for the largest commercial fleets. Sets of four columns provide 56,000- or 76,000-pound total capacity , and columns can operate individually, in pairs, or as a synchronized group of up to eight. A 10-inch touchscreen on any column serves as the master control, offering built-in diagnostics and system browsing for quick vehicle troubleshooting.

SPECIFICATIONS

SPECIFICATION	800 SERIES WIRELESS MOBILE COLUMN LIFT
Lift Speed (Max Load)	60" per min.
Length of Lift Unit	53.625"
Width of Lift Unit	44.25"
Height of Lift Unit	88.5"
Height of Lift Unit at Full Rise	157.125"
Operating Peak Power	4HP
Operating Voltage	24 VDC Nominal
Charger Voltage Required	120 VAC @ 60 Hz
Charger Amps Required	1.3 amps
Max. Lift Height (4 or more units)	69"
Max. Lift Height (2 units – Wheel Lift Mode)	32"
Min-Max Wheel Diameter	5" – 24.5"
Footprint of Lift Unit	560 sq in.
Turning Radius of Lift Unit	47"

Specifications published by the Mohawk factory and subject to change. Source: mohawklifts.com.