



MOHAWK

Mohawk A7 Two-Post Lift

Asymmetric Two-Post Automotive Lift

7,000 LBS. CAPACITY

Contact for Pricing

The Mohawk A-7 Two Post Lift is a heavy-duty, American-made lifting solution engineered for professional automotive shops, fleet garages, and performance vehicle facilities. With a 7,000 lb. lifting capacity, it combines heavy duty construction, low-profile arms, and industry-leading safety systems — making it ideal for everything from low-clearance EVs to light trucks and SUVs.

7,000 lbs.
CAPACITY

6' under arm
RISE HEIGHT

45 seconds at full load
(faster with lighter load)
FULL RISE

2.0 HP/208-230V, Single-phase (3ø optional)
POWER

OVERVIEW

Mohawk's A-7 stands apart with columns made from $\frac{3}{4}$ " thick forklift mast steel — delivering unmatched durability, strength, and resistance to flex or fatigue. Unlike lifts built from formed sheet metal, this one is built to take decades of use in high-demand environments.

SPECIFICATIONS

SPECIFICATION	A7 TWO-POST LIFT
Lifting Capacity	7,000 lbs.
Lifting Height	6' under arm
Lifting Speed	45 seconds at full load (faster with lighter load)
Overall Width (adjustable)	11' 7"
Column Height	7' 11 1/2"
Width Between Posts	7' 7 1/8" to 8' 1 1/8"
Arm Pad Height	4"
Lift Pad Height @ Full Rise	6' 4"
Lift Pad Height @ Full Rise w/Adaptors	7' 1"
3" Frame Adaptors (stackable)	4 included as standard equipment
6" Frame Adaptors (stackable)	4 included as standard equipment
Synchronization	Hydraulic fluid displacement using no chains, cables, or overhead obstructions
Mechanical Safety Locks	Automatic; all position starting at 3"
Hydraulic Safety Systems	Automatic; all position
Swing Arm Restraints	Automatic upon ascent (starting at 4")
Cylinders	2 (1 per column)
Drive System	#646 leaf chain routed over cylinder
Steel Carriage Bearings	8 per carriage, double sealed, selflubricating
Motor Rating	2.0 HP/208-230V,Single-phase (3ø optional)
Overhead Hydraulic Line Height	12' Standard (adjustable to accommodate any height ceiling or routed in-floor)
Concrete Floor Requirements	4000 psi (27579.02 kPa) mix 4 1/2"
Anchoring System (included)	(14) 3/4"x5" bolts
Floor Access Between Posts	Clear and unobstructed
Weight	2,000 lbs.
Warranty	25 years structural, 10 year mechanical, plus limited lifetime cylinder seal warranty
Width Between Lifting Arms	6' 11 3/8" to 7' 5 3/8"

Specifications published by the Mohawk factory and subject to change. Source: mohawklifts.com.