



MOHAWK

# Mohawk Car Storage & Service Lift

Two-Post Car Storage & Service Lift  
**10,000 LBS. CAPACITY**

## Contact for Pricing

Mohawk car storage and vehicle service lifts are built for versatility, combining professional-grade lifting with efficient automotive storage . With the wheel adapter kit, Mohawk 10,000–18,000 lb. 2-post lifts seamlessly support both vehicle service and space-saving car storage in one dependable system.

**10,000 lbs.**  
CAPACITY

**6' under arm**  
RISE HEIGHT

**50 seconds at full load**  
(faster with lighter load)  
FULL RISE

**2.0 HP/208-230V,Single-**  
**phase (3ø optional)**  
POWER

## OVERVIEW

With the optional wheel adapter kit, Mohawk 2-post lifts in the 10,000–18,000 lb. capacity range transition seamlessly from service applications to automotive storage. The result is a versatile lift system that delivers the strength, stability, and safety needed for working on vehicles, while also providing a reliable way to maximize floor space in garages, shops, and facilities where efficiency matters.

## SPECIFICATIONS

| SPECIFICATION                          | CAR STORAGE & SERVICE LIFT                                                              |
|----------------------------------------|-----------------------------------------------------------------------------------------|
| Lifting Capacity                       | 10,000 lbs.                                                                             |
| Lifting Height                         | 6' under arm                                                                            |
| Lifting Speed                          | 50 seconds at full load (faster with lighter load)                                      |
| Overall Width (adjustable)             | 11' 10"                                                                                 |
| Column Height                          | 8' 7"                                                                                   |
| Width Between Posts                    | 10' (adjustable)                                                                        |
| Arm Pad Height                         | 3 ½"                                                                                    |
| Lift Pad Height @ Full Rise            | 6' 3 ½"                                                                                 |
| Lift Pad Height @ Full Rise w/Adaptors | 7' ½"                                                                                   |
| 3" Frame Adaptors (stackable)          | 4 included as standard equipment                                                        |
| 6" Frame Adaptors (stackable)          | 4 included as standard equipment                                                        |
| Synchronization                        | Hydraulic fluid displacement using no chains, cables, or overhead obstructions          |
| Mechanical Safety Locks                | Automatic; all position starting at 5"                                                  |
| Hydraulic Safety Systems               | Automatic; all position                                                                 |
| Swing Arm Restraints                   | Automatic upon ascent                                                                   |
| Cylinders                              | 2 (1 per column)                                                                        |
| Drive System                           | #646 leaf chain routed over cylinder                                                    |
| Thrust & Guide Bearings                | (16) 4" diameter, (8 per carriage) double sealed, self-lubricating ball bearing rollers |
| Motor Rating                           | 2.0 HP/208-230V,Single-phase (3ø optional)                                              |
| Overhead Hydraulic Line Height         | 12' Standard (adjustable to accommodate any height ceiling or routed in-floor)          |
| Concrete Floor Requirements            | 4000 psi (27579.02 kPa) mix 61/2"                                                       |
| Anchoring System (included)            | (16) ¾"x5" bolts                                                                        |
| Floor Access Between Posts             | Clear and unobstructed                                                                  |
| Weight                                 | 2,500 lbs.                                                                              |
| Warranty                               | 25 years structural, 10 year mechanical, plus limited lifetime cylinder seal warranty   |
| Width Between Lifting Arms             | 8' 10" (adjustable)                                                                     |

Specifications published by the Mohawk factory and subject to change. Source: [mohawklifts.com](http://mohawklifts.com).