



MOHAWK

Mohawk FL-25 Drive-On Forktruck Lift

Drive-On Forktruck Lift

25,000 LBS CAPACITY

Contact for Pricing

The Mohawk FL-25 delivers 25,000 pounds of lifting capacity and a full six-foot rise for complete undercarriage access during forklift service and maintenance. This surface-mounted lift bolts directly to your shop's concrete floor and can be installed in just a few hours. Adjustable runways easily accommodate forklifts of any wheelbase or length , making the FL-25 a versatile solution for facilities that service a wide range of industrial trucks.

25,000 lbs
CAPACITY

**2 HP/220 V Single-Phase (3
phase optional)**
POWER

OVERVIEW

The FL-25 delivers a full 25,000-pound capacity in a compact, above-ground design—no pits or in-ground cylinders required. Installation is fast and straightforward, and the open layout provides complete undercarriage access with a lifting height of more than 5 feet 9 inches. Adjustable 24-inch runways easily accommodate forklifts of every size, and custom configurations are available for unique industrial requirements.

SPECIFICATIONS

SPECIFICATION	FL-25 DRIVE-ON FORKTRUCK LIFT
Lifting Capacity	25,000 lbs
Overall Length	20'-3 1/16"
Overall Width	12'-6 3/16"
Clearance Between Posts	11' Standard (Wider Available)
Mechanical Safety Release	Single Point
Mechanical Safety Locks	Multi-Positions
Back-Up Hydraulic Safety Systems	Pressure Compensated Flow Controls & Velocity Fuses
Motor Rating	2 HP/220 V Single-Phase (3 phase optional)
Concrete requirements	4,000 PSI concrete 4 ½" thick floor
Lift Weight	4,200 lbs
Warranty	3 years; (Excluding Motor/Pump)
Lifting Mechanism	5" Hydraulic Cylinder Attached to (4) #646 Leaf Chains
Track Length	20'
Lifting Stroke	5'
Height @ Full Stroke	5'-9 5/16" (top of runways)
Track Width	24"
Track Adjustment	4' to 8'

Specifications published by the Mohawk factory and subject to change. Source: mohawklifts.com.