



MOHAWK

Mohawk Lift LC12

12,000 lb Two-Post Truck Lift

12,000 LBS. CAPACITY

Contact for Pricing

The Mohawk LC-12 Two Post Lift is a low-ceiling, clear-floor above-ground lift engineered for exceptional performance and safety. Designed to handle light- to medium-duty vehicles up to 12,000 lbs , the LC-12 is the ideal solution for shops working with a variety of cars, trucks, and service vehicles.

12,000 lbs.

CAPACITY

6' under arm

RISE HEIGHT

**80 seconds at full load
(faster with lighter load)**

FULL RISE

**2.5 HP/208-230V, Single-
phase (3Ø optional)**

POWER

OVERVIEW

Each lift carriage rolls on eight double-sealed, self-lubricating steel ball bearing rollers , offering smooth, maintenance-free performance—far superior to the plastic sliders used in other lifts. Built with 3/4" thick forklift mast steel columns , the LC-12 delivers unmatched structural strength and durability that stands up to the demands of continuous commercial and fleet use.

SPECIFICATIONS

SPECIFICATION	LIFT LC12
Lifting Capacity	12,000 lbs.
Lifting Height	6' under arm
Lifting Speed	80 seconds at full load (faster with lighter load)
Overall Width (adjustable)	12' 7"
Column Height	8' 7"
Width Between Posts	10' (adjustable)
Arm Pad Height	5"
Lift Pad Height @ Full Rise	6' 5"
Lift Pad Height @ Full Rise w/Adaptors	7'3"
5" Frame Adaptors (stackable)	4 included as standard equipment
7 1/2" Frame Adaptors (stackable)	4 included as standard equipment
10" Frame Adaptors (stackable)	4 included as standard equipment
Synchronization	Hydraulic fluid displacement using no chains, cables, or overhead obstructions
Mechanical Safety Locks	Automatic; all position starting ground level
Hydraulic Safety Systems	Automatic; all position
Swing Arm Restraints	Automatic upon ascent
Cylinders	2 (1 per column)
Drive System	#BL-848 leaf chain routed over cylinder
Thrust & Guide Bearings	(16) 4" diameter, (8 per carriage) double sealed, self-lubricating ball bearing rollers
Motor Rating	2.5 HP/208-230V,Single-phase (3Ø optional)
Overhead Hydraulic Line Height	12' Standard (adjustable to accommodate any height ceiling or routed in-floor)
Concrete Floor Requirements	4000 psi (27579.02 kPa) mix 61/2"
Anchoring System (included)	(16) ¾"x6" bolts
Floor Access Between Posts	Clear and unobstructed
Weight	2,900 lbs.
Warranty	25 years structural, 10 year mechanical, plus limited lifetime cylinder seal warranty
Width Between Lifting Arms	8' 10" (adjustable)
Standard Base	6 ½" of 4,000 psi concrete

Specifications published by the Mohawk factory and subject to change. Source: mohawklifts.com.