



MOHAWK

Mohawk ML-220 Two-Post Lift

20,000 lb Two-Post Heavy-Duty Vehicle Lift

20,000 LBS. CAPACITY

Contact for Pricing

The Mohawk ML-220 is a true workhorse among above-ground lifts. Engineered for power and precision, this clear-floor lift is built to handle light- and medium-duty vehicles with capacities up to 20,000 lbs. Its rugged twin-cylinder, direct-drive design eliminates the need for chains, cables, pulleys, or equalizer bars—reducing wear and maintenance while delivering smooth, synchronized lifting every time.

20,000 lbs.
CAPACITY

6' under arm
RISE HEIGHT

90 seconds at full load
(faster with lighter load)
FULL RISE

3 HP/208-230V, Single-phase (3ø optional)
POWER

OVERVIEW

Mohawk auto lifts are engineered for long-term performance in the most demanding service environments. Each lift features columns made from $\frac{3}{4}$ -inch thick forklift masts, delivering unmatched strength and reliability over a lifetime of use. Unlike competitors that use plastic slide blocks, Mohawk's carriages glide smoothly on eight double-sealed, self-lubricating steel ball bearing rollers—eliminating friction, wear, and the need for ongoing maintenance.

SPECIFICATIONS

SPECIFICATION	ML-220 TWO-POST LIFT
Lifting Capacity	20,000 lbs.
Lifting Height	6' under arm
Lifting Speed	90 seconds at full load (faster with lighter load)
Overall Width (adjustable)	12' 7 ½" (adjustable)
Column Height	8' 7"
Width Between Posts	10' (adjustable)
Arm Pad Height	4.5"
Lift Pad Height @ Full Rise	6' 5"
Lift Pad Height @ Full Rise w/Adaptors	7'3" (includes 5", 7 ½" and 10" stackable lift adaptor pads)
5" Frame Adaptors (stackable)	4 included as standard equipment
7 1/2" Frame Adaptors (stackable)	4 included as standard equipment
10" Frame Adaptors (stackable)	4 included as standard equipment
Synchronization	Hydraulic fluid displacement using no chains, cables, or overhead obstructions
Mechanical Safety Locks	Automatic; all position starting ground level
Hydraulic Safety Systems	Automatic; all position
Swing Arm Restraints	Automatic upon ascent
Cylinders	2 (1 per column)
Drive System	#BL-848 leaf chain routed over cylinder
Thrust & Guide Bearings	(16) 4" diameter, (8 per carriage) double sealed, self-lubricating ball bearing rollers
Motor Rating	3 HP/208-230V, Single-phase (3ø optional)
Overhead Hydraulic Line Height	15' Standard (adjustable to accommodate any height ceiling or routed in-floor)
Concrete Floor Requirements	4000 psi (27579.02 kPa) mix 61/2"
Anchoring System (included)	(16) ¾"x6" bolts
Floor Access Between Posts	Clear and unobstructed
Weight	4,100 lbs.
Warranty	25 years structural, 10- year mechanical, plus limited lifetime cylinder seal warranty
Width Between Lifting Arms	8' 9 ¾" (adjustable)
Wide Base	5 ½" of 4,000 psi concrete
Standard Base	6 ½" of 4,000 psi concrete

Specifications published by the Mohawk factory and subject to change. Source: mohawklifts.com.