



TOOL & EQUIPMENT CONNECTION, INC.
BUILD YOUR ULTIMATE GARAGE



MOHAWK

Mohawk Vertical Rise Lift

Heavy-Duty Vertical Rise Vehicle Lift

Contact for Pricing

Mohawk's Vertical Rise Lifts handle the largest commercial and municipal vehicles with capacities from 35,000 to 99,000 pounds and track lengths from 20 to 48 feet . Each model can be installed surface-mounted or flush-mounted , allowing the runways to sit level with the shop floor when fully lowered for a seamless, unobstructed work area .

OVERVIEW

Mohawk Vertical Rise Lifts are engineered to handle the largest commercial and municipal vehicles, with capacities from 35,000 to 99,000 pounds and track lengths ranging from 20 to 48 feet . Available as surface-mounted, recessed pit, or flush-mounted systems , these lifts provide a towering 79–82 inches of rise—up to 13 inches higher than competing models—for complete, unobstructed under-vehicle access . Optional rolling jacks (26,400 to 44,000 lb.

SPECIFICATIONS

SPECIFICATION	VERTICAL RISE LIFT
Lifting Speed	70 Seconds (faster with lighter load)
Safety Locks	Start at 18" off the ground and then a lock position every 3.5" after that
Approach Ramp Length	101.6" – standard
Air Pneumatic	60 – 120 PSI
Concrete Floor Requirements	Minimum – 6" / 4000 PSI
Track Lengths	23'- 48' (other lengths also available)
Width Between Track Std	46.5" (adjustable)

Specifications published by the Mohawk factory and subject to change. Source: mohawklifts.com.