

MOHAWK COLUMN LIFTS

18,000, 24,000, 30,000 LBS. PER COLUMN CAPACITIES

*Mohawk AC or DC
Operated Mobile
Column Lifts*



Model Shown:
MP-18-030

TO MEET THE ONE
AND ONLY NATIONAL
SAFETY STANDARD
FOR VEHICLE LIFTS



MOHAWK

Americas Best Lift Investment...

Still proudly designed, welded
and manufactured in the U.S.A.



MP-18 SPECIFICATIONS

	MP-18-15	MP-18-22
Capacity:		
Capacity per post	18,000 lbs.	16,000 lbs.
Lifting speed:	66 sec.	66 sec.
Motor rating (per column):	2.5 H.P.	2.5 H.P.
Standard power requirement:	208/240 V or optional 440/480 V 3 phase (single phase option available) or 24 volt DC operations	
Amperage requirements:	10 AMPS (per post AC)	
Lifting height (stroke):	67"	67"
Lifting mechanism:	Direct drive hydraulic cylinders	
Cylinder protection:	Full steel enclosure	
Clearance between carriage & vehicle:	10"	10"
Carriage movement:	Double sealed roller bearings	
Synchronization:	Automatic SIEMENS® PLC controlled [AC] Automatic Horner Electric PLC controlled [DC]	
Lifting forks range:	13" to 24" wheels [wider optional]	
Lifting fork height/angle:	3 1/2" and 28 degrees	
Maximum tire diameter:	48" [wider optional]	
Front wheels:	6 5/8" with sealed roller bearings at center	
Steering system:	Pallet jack mech. w/OSHA approved handle & pressure relief valve	
Mechanical safety locks:	19 position starting at 12"	
External hydraulic safety systems:	Pressure compensated flow control valving & velocity fuses	
Electrical safety systems:	Electronic sensors in each column	
Floor requirement:	Any hard, level surface [3° max floor slope]	
Control voltage:	24 volts	24 volts
Warranty:	3 years	

Available Options

- Mobile jack stands (spring assisted)

Model	Range	Capacity per stand
MJS18-30-18/24	18" TO 30"	18,000 or 24,000
MJS30-47-18/24	25" TO 47"	18,000 or 24,000
MJS47-75-18/24	45" TO 77"	18,000 or 24,000

- Chassis contact lifting beam
- Longer forks
- 460 or 575 volt power units
- Lifting height limiter
- Single phase power
- Double wide columns
- Front to rear bumper adaptor
- Heavier capacities on request
- Winged snow plow adaptor
- Wider carriages
- Safety weight gauge
- Runways & approach ramps
- Remote pendant control
- Fork lift adaptor kit
- Automotive frame contact adaptor
- Slope indicator

Mohawk builds the best products with the finest materials, to the highest standards. Just compare our lifts. Our staff will assist you with any technical questions you have. We invite your calls.

Mohawk lifts are manufactured in compliance with the following standards:
ALI, ANSI, ASME, AISI, ASTM, ASA, NEC, AWG, NEMA.

MEETS CURRENT NATIONAL ANSI SAFETY CODE FOR LIFTS.



AVAILABLE UNDER
DISCOUNTED
GOVERNMENT CONTRACT
IN ALL 50 STATES




GSA
contract
#GS-07F-
207AA



Mohawk Resources, LTD.
P.O. Box 110
65 Vrooman Ave
Amsterdam, NY 12010
(800) 833-2006
(518) 842-1431
FAX: (518) 842-1289
www.mohawklifts.com

Mohawk MP-18 Specifications



specifications subject to change without notice



www.mohawklifts.com/specs



For more detailed product information read
this free e-book "How a Mohawk Mobile
Column Lift is Made" at
www.mohawklifts.com/Mobile-Column-Lifts



www.facebook.com/mohawklifts

DISTRIBUTED BY: