



CHALLENGER

Challenger EV1020XP9 Inground Drive-On Pad Lift

9K Inground Drive-On Pad Lift

9,000 LBS. CAPACITY

Contact for Pricing

Challenger's 9,000-lb. drive-on-style pad aids in quick vehicle spotting in express bays. This add-on configuration provides the quickest vehicle loading, reducing frustration in shops.

FEATURES

- Long bearing contact provides increased stability
- Stainless steel air lock release cylinder promotes longer working life with its corrosion resistant design
- Premium powder coat finish on bolsters provides long-lasting durability
- Mechanical lock engages every 3", allowing ergonomic working height for technicians to increase productivity and minimize fatigue
- QuickCycle™ models reduce vehicle travel time by 30 percent

SPECIFICATIONS

SPECIFICATION	EV1020XP9
Lifting Capacity	9,000 lbs.
Arms	n/a
Stroke	68"
Rise Height	70"
Width Overall	79.75"
Drive-Thru Clearance	-
Reach (Arm Minimum)	-
Reach (Arm Maximum)	-
Screw Pad Height	Minimum Pad Height: 2.25"

SPECIFICATION	EV1020XP9
Capacity	4,500 lb. per pad
Guide Plunger Diam.	8.5"
Motor / Voltage	2HP, 208v-230v, 60Hz, 1Ph
Speed of Rise	38 s
Air Required	90 – 120 psi
ALI/ETL Certified	Yes
Super Structure Colors	Black

Specifications published by the Challenger factory and subject to change. Source:

challengerlifts.com.