

MOHAWK

Mohawk TP-26 / TP-30 Two-Post Lift

26,000 / 30,000 lb Two-Post Truck Lift

26,000 LBS. / 30,000 LBS. CAPACITY

Contact for Pricing

When it comes to strength, safety, and serviceability , the Mohawk TP-26 and TP-30 two-post lifts stand in a league of their own. Designed to handle vehicles up to 30,000 lbs. , these industry-leading lifts are engineered for reliability, long-term performance, and shop efficiency . Whether you're servicing medium-duty fleet trucks or full-size utility vehicles, Mohawk's rugged lift design delivers unmatched stability and access

26,000 lbs. / 30,000 lbs. CAPACITY	**6' under arm** RISE HEIGHT	**135 seconds** FULL RISE	**5 HP 208-230v or 440-480v 3ø** POWER

OVERVIEW

Crafted from 7" wide by 1" thick forklift mast channel steel —not formed sheet metal—the TP-26 and TP-30 deliver the kind of durability that lasts for decades . Each lift is surface-mounted, eliminating the need for in-ground installation, tanks, or disruptive excavation. This not only simplifies setup but makes maintenance more accessible.

SPECIFICATIONS

SPECIFICATION	TP-26 / TP-30 TWO-POST LIFT
Lifting Capacity	26,000 lbs. / 30,000 lbs.
Lifting Height	6' under arm
Lifting Speed	135 seconds
Overall Width (adjustable)	15' (wider base model 17')
Column Height	11'
Width Between Posts	12'
Arm Pad Height	7"
Lift Pad Height @ Full Rise w/Adaptors	7' 5"
5" Frame Adaptors (stackable)	4 included as standard equipment
7 1/2" Frame Adaptors (stackable)	4 included as standard equipment
10" Frame Adaptors (stackable)	4 included as standard equipment
Synchronization	Hydraulic fluid displacement using no chains, cables, or overhead obstructions
Mechanical Safety Locks	Multi-position, interlocked redundant safety systems
Hydraulic Safety Systems	Automatic; all position
Swing Arm Restraints	Automatic upon ascent
Cylinders	2 (1 per column)
Drive System	#BL-848 leaf chain routed over cylinder
Carriage Bearings	(16) 5" (12.7 cm) diameter (8 per carriage) Double sealed self lubricating
Side Load Bearings	(8) 5" (12.7 cm) diameter (4 per Carriage) Double sealed self lubricating
Motor Rating	5 HP 208-230v or 440-480v 3ø
Overhead Hydraulic Line Height	16' Standard (adjustable to accommodate any height ceiling or routed in-floor)
Concrete Floor Requirements	4000 psi (27579.02 kPa)
Anchoring System (included)	12" floor: (18) 1" x 10" Wej-it bolts, 8" floor: (28) 1" x 8" Wej-it bolts
Floor Access Between Posts	Clear and unobstructed
Weight	8,800 lbs. / 9,300 lbs.
Warranty	25 years structural, 10 year mechanical, plus limited lifetime cylinder seal warranty
Arm Height @ Full Rise	6' 7"
Width Between Carriage	9' 9"
Wide Base	TP-26/30 WB: 8" of 4000 psi concrete
Standard Base	TP-26/30: 12" of 4000 psi concrete

Specifications published by the Mohawk factory and subject to change. Source: mohawklifts.com.